



POMPA CIEPŁA R290-060-3P-DTU

KRZYWE WYDAJNOŚCI

Wydajność grzewcza nominalna (kW)

Wyjście wody (°C)	-30	-25	-20	-16	-15	-12	-7	-5	0	1	2	5	7	10	14	15	20	25	30	35
35	/	8.91	10.77	12.39	12.84	15.16	17.75	18.90	20.34	20.50	21.10	21.70	22.00	23.37	23.10	23.45	25.47	26.04	25.37	27.66
41	/	8.68	10.46	12.04	12.45	13.09	15.38	16.28	18.30	18.46	19.02	19.52	19.81	21.15	21.20	21.50	23.37	23.45	25.39	26.43
45	/	8.47	10.23	11.77	12.18	12.81	14.96	15.92	17.91	18.06	18.60	19.09	19.36	20.56	20.42	20.71	22.65	22.92	24.97	25.97
50	/	8.28	9.93	11.43	11.83	12.44	14.51	15.45	17.37	17.52	18.04	18.51	18.78	19.93	18.20	18.47	20.07	22.23	24.19	25.25
55	/	7.97	9.62	11.07	11.46	11.18	13.03	13.87	15.52	15.64	16.11	16.54	16.76	17.92	17.53	17.77	19.30	19.84	22.10	24.66
60	/	7.83	9.28	10.60	10.97	9.92	11.60	12.35	14.95	15.09	15.53	15.93	16.16	17.11	16.69	16.92	18.92	19.13	21.29	24.27
65	/	/	8.31	9.51	9.83	9.52	11.13	11.85	12.78	12.88	13.26	14.02	14.22	15.05	15.26	15.48	16.81	16.83	18.11	17.25
70	/	/	/	9.06	9.38	9.08	10.60	11.23	12.19	12.29	12.66	13.35	13.56	14.32	14.53	14.73	16.00	16.05	17.23	16.41
75	/	/	/	/	/	/	10.03	10.63	11.01	11.48	11.85	12.63	12.96	13.51	13.69	13.90	15.07	/	/	/

Pobór mocy elektrycznej (kW)

Wyjście wody (°C)	-30	-25	-20	-16	-15	-12	-7	-5	0	1	2	5	7	10	14	15	20	25	30	35
35	/	4.29	4.38	4.43	4.43	4.64	4.73	4.77	4.89	4.93	4.96	4.98	5.02	5.07	4.51	4.51	4.56	4.43	3.53	3.62
41	/	4.54	4.65	5.00	5.15	5.19	5.34	5.40	5.17	5.19	5.22	5.23	5.25	5.26	4.62	4.65	4.69	4.31	3.74	3.79
45	/	4.68	4.82	5.20	5.37	5.43	5.47	5.53	5.62	5.50	5.50	5.12	5.20	5.30	4.96	4.97	4.91	4.52	4.07	4.10
50	/	4.82	4.96	5.34	5.50	5.59	5.73	5.76	5.85	5.73	5.74	5.45	5.44	5.57	5.19	5.21	5.21	4.83	4.38	4.39
55	/	4.93	5.11	5.50	5.68	5.23	5.31	5.39	5.55	5.56	5.56	5.61	5.65	5.67	4.95	4.99	5.04	4.59	4.60	4.64
60	/	5.85	5.95	6.01	6.11	5.57	5.61	5.73	5.97	6.00	6.03	6.04	6.06	6.07	5.29	5.31	5.32	5.46	4.96	5.01
65	/	/	6.35	6.44	6.53	6.27	6.49	6.67	6.44	6.32	6.35	6.26	6.26	6.42	5.95	5.97	6.01	5.88	5.70	5.71
70	/	/	/	6.75	6.92	7.06	7.21	7.46	7.25	7.13	7.17	7.05	7.07	7.26	6.72	6.76	6.82	6.71	6.04	6.09
75	/	/	/	/	/	/	7.82	7.71	7.07	7.15	7.17	7.24	7.27	7.40	7.21	7.25	7.28	/	/	/

COP

Wyjście wody (°C)	-30	-25	-20	-16	-15	-12	-7	-5	0	1	2	5	7	10	14	15	20	25	30	35
35	/	2.08	2.46	2.80	2.90	3.27	3.75	3.96	4.16	4.16	4.25	4.36	4.38	4.61	5.12	5.20	5.59	5.88	7.19	7.63
41	/	1.91	2.25	2.41	2.42	2.52	2.88	3.02	3.54	3.56	3.65	3.73	3.78	4.02	4.59	4.62	4.98	5.44	6.79	6.98
45	/	1.81	2.12	2.26	2.27	2.36	2.73	2.88	3.18	3.28	3.38	3.72	3.73	3.88	4.11	4.16	4.61	5.07	6.13	6.33
50	/	1.72	2.00	2.14	2.15	2.23	2.53	2.68	2.97	3.05	3.14	3.40	3.45	3.58	3.50	3.55	3.85	4.60	5.53	5.75
55	/	1.62	1.88	2.01	2.02	2.14	2.46	2.57	2.80	2.81	2.90	2.95	2.97	3.16	3.54	3.56	3.83	4.32	4.80	5.32
60	/	1.34	1.56	1.76	1.80	1.78	2.07	2.15	2.51	2.52	2.58	2.64	2.67	2.82	3.15	3.19	3.56	3.51	4.29	4.85
65	/	/	1.31	1.48	1.51	1.52	1.71	1.78	1.99	2.04	2.09	2.24	2.27	2.34	2.56	2.59	2.80	2.86	3.18	3.02
70	/	/	/	1.34	1.36	1.29	1.47	1.50	1.68	1.72	1.77	1.89	1.92	1.97	2.16	2.18	2.34	2.39	2.85	2.69
75	/	/	/	/	/	/	1.28	1.38	1.56	1.60	1.65	1.74	1.78	1.82	1.90	1.92	2.07	/	/	/

THERMATEC | Home Star Sp. z o.o.
 ul. Misjonarzy Oblatów MN 20A
 40-129 Katowice



PIECZĄTKA DYSTRYBUTORA